ELECTRIAL CONTACT PRESSURE GAUGE
Model: P520 series

Spec. sheet no. PD05-04

Service intended
P520 series are designed for a local reading of measured pressure and equipped with the inductive contact block which allows all the combinations of contacts to be used. The contact block is mounted on the dial. The window is fitted with a knob for external adjustment of the setpoints.

Nominal diameter
100 mm

Accuracy
±1.0% of full scale

Scale range (MPa, kPa, bar)
-0.1 ~ 0 to 0 ~ 200 MPa

Working pressure
Steady : 100 % of full scale
Over range protection : 130 % of full scale

Working temperature
Ambient : -40 ~ 65 °C
Fluid : Max. 200 °C

Degree of protection
EN60529/IEC529/IP67

Temperature effect
Accuracy at temperature above and below the reference temperature (20 ℃) will be effected by approximately ±0.4 % per 10 ℃ of full scale



Standard features

Pressure connection
Stainless steel (316SS)

Element
Stainless steel (316SS)
<10 MPa : C type bourdon tube
≥10 MPa : Helical type bourdon tube

Case
Stainless steel (304SS)

Cover
Stainless steel (304SS)
Bayonet type

Window
Safety glass

Movement
Stainless steel

Dial
White aluminium with black graduations

Pointer
Black painted aluminium alloy

Conduit connection
M20 x 1.5

Process connection
⅜", ½" PT, NPT and PF

Certificates
Pressure equipment directive (2014/68/EU) Annex III Module H

Option
Damping movement

Main order — Ordering information

1. Base model

P520	Electrical contact type pressure gauge

2. Nominal diameter (mm)

4	100

3. Type of mounting

A	Bottom connection, direct
B	Bottom connection, surface, case mounting plate
G	Lower back connection, direct
N	Lower back connection, flush, cover mounting plate

4. Contact function

1	High alarm, normal open contact
2	Low and High alarm
3	Low alarm, normal close contact
4	Two high alarm
5	Two low alarm
6	Failsafe high and low alarm

5. Process connection

D	⅜"
E	½"

6. Connection type

B	PF
C	PT
D	NPT
F	BSPT
G	BSP
Z	Other

7. Unit

H	bar
I	MPa
J	kPa

8. Range

XXX	Refer to pressure unit and range table

9. Pressure connection material and dial color

3	316SS and 2 colors
7	316SS and 3 colors

10. Option

0	None
1	Accessories


Sample ordering code

1	2	3	4	5	6	7	8	9	10
P520	**4**	**A**	**3**	**D**	**D**	**H**	**XXX**	**3**	**0**


© WISE Control Inc. All rights reserved. ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

P520 : Type of mounting


Code A




Code B



Code G



Code N



Snap - action contacts

General

Electromechanical limit switches in pointer type measuring instruments are auxiliary current switches which open or close electrical circuits at set limit values by means of a contact arm which is moved by the actual value pointer.
The snap action contact is a mechanical contact for switching capacities up to 30 W 50 VA max.
Contact making will be delayed and or advanced in relation to the movement of the actual value pointer.
To closed the circuit, the contact pin of the movable contact arm is attracted in a jump by the permanent magnet fastened to the supporting arm shortly before the set value has been reached.
Due to the retention force of the magnet, snap action contacts are more resistant against shock and vibration.
The switching safety is increased by the increased contact pressure.
When the citcuit is opened, the magnet keeps the contact arm in its place until the restoring force of the measuring element exceeds the magnetic force, and the contact opens in a jump.

Specifications







Maximum contact rating with non-inductive (ohmic) load		**Electrical contacts type pressure gauge model P520 series**
		Dry gauges
Maximum voltage		250 V
Current ratings	**Make ratings**	1.0 A
	Break ratings	1.0 A
	Continuos load	0.6 A
Maximum load		30 W 50 VA
Material of contact points		Silver-Nickel alloy (80 % Ag / 20 %Ni / 10 µm) gold-plated
Ambient operating temperature		-20...+70 °C
Max. no. of contacts		2
Voltage test		Circuit / protective earth conductor - 2,000 vac 1 minute
		Circuit /circuit - 2,000 vac 1 minute

Recommended contact ratings with ohmic and inductive load


Voltage (DIN IEC 38) DC / AC	**Electrical contacts type pressure gauge model P520 series**		
	Dry gauges		
	Ohmic load		Inductive load
	DC	AC	
			cosØ > 0.7
V	mA	mA	mA
220 / 230	100	120	65
110 / 110	200	240	130
48 / 48	300	450	200
24 / 24	400	600	250

In order to ensure a high switching reliability of the contacts the switching voltage should not be below 24 V, also taking environmental influences in the long term into account.

Contact function table

CODE	Wiring Scheme		Contact Function		Wiebrock Code No.	Remark
			1st Contact	2nd Contact		
Single Contact						
1	Contact make when pointer reachse setpoint (Normal open - NO)				S/M-1	Normal use high alarm system
3	Contact break when pointer reachse setpoint (Normal close - NC)				S/M-2	Normal use low alarm system
Double Contact - Common Circuit						
4	1st and 2nd contact make when pointer reaches setpoint				S/M-11	Normal use two high alarm system
6	1st contact make 2nd contact break when pointer reaches setpoint				S/M-12	Normal use failsafe high and low alarm system
2	1st contact break 2nd contact make when pointer reaches setpoint				S/M-21	Normal use Low and High alarm system
5	1st and 2nd contact break when pointer reaches setpoint				S/M-22	Normal use two low alarm system

Terminal block arrangement



1. High alarm (S/M-1)

① Normal open
② Common
④ Ground

2. Low and high alarm (S/M-21)

Low alarm

① Normal close
② Common
④ Ground

High alarm

② Common
③ Normal open

3. Low alarm (S/M-2)

① Normal close
② Common
④ Ground

4. Two high alarm (S/M-11)

No.1 High alarm

① Normal open
② Common
④ Ground

No.2 High alarm

② Common
③ Normal open

5. Two low alarm (S/M-22)

No.2 Low alarm

① Normal close
② Common
④ Ground

No.1 Low alarm

② Common
③ Normal close

6. Failsafe high and low alarm (S/M-12)

High alarm

② Common
③ Normal close
④ Ground

Low alarm

① Normal open
② Common

Pressure unit and range table

Range and code	Unit and code			Nominal diameter
	H : bar	I : MPa	J : kPa	100 mm
026	-1 ~ 0	-0.1 ~ 0	-100 ~ 0	O
041	0 ~ 1	0 ~ 0.1	0 ~ 100	O
133	0 ~ 1.6	0 ~ 0.16	0 ~ 160	O
042	0 ~ 2	0 ~ 0.2	0 ~ 200	O
134	0 ~ 2.5	0 ~ 0.25	0 ~ 250	O
043	0 ~ 3	0 ~ 0.3	0 ~ 300	O
044	0 ~ 4	0 ~ 0.4	0 ~ 400	O
045	0 ~ 6	0 ~ 0.6	0 ~ 600	O
047	0 ~ 10	0 ~ 1	0 ~ 1,000	O
050	0 ~ 15	0 ~ 1.5	X	O
143	0 ~ 16	0 ~ 1.6	X	O
051	0 ~ 20	0 ~ 2	X	O
052	0 ~ 25	0 ~ 2.5	X	O
054	0 ~ 35	0 ~ 3.5	X	O
151	0 ~ 40	0 ~ 4	X	O
055	0 ~ 50	0 ~ 5	X	O
056	0 ~ 60	0 ~ 6	X	O
057	0 ~ 70	0 ~ 7	X	O
058	0 ~ 100	0 ~ 10	X	O
059	0 ~ 150	0 ~ 15	X	O
060	0 ~ 160	0 ~ 16	X	O
062	0 ~ 250	0 ~ 25	X	O
064	0 ~ 350	0 ~ 35	X	O
065	0 ~ 400	0 ~ 40	X	O
066	0 ~ 500	0 ~ 50	X	O
067	0 ~ 600	0 ~ 60	X	O
068	0 ~ 700	0 ~ 70	X	O
070	0 ~ 1,000	0 ~ 100	X	O
074	0 ~ 1,600	0 ~ 160	X	O
075	0 ~ 2,000	0 ~ 200	X	O
027	-1 ~ 1	-0.1 ~ 0.1	-100 ~ 100	O
127	-1 ~ 1.5	-0.1 ~ 0.15	-100 ~ 150	O
028	-1 ~ 2	-0.1 ~ 0.2	-100 ~ 200	O
029	-1 ~ 3	-0.1 ~ 0.3	-100 ~ 300	O
030	-1 ~ 4	-0.1 ~ 0.4	-100 ~ 400	O
010	-1 ~ 5	-0.1 ~ 0.5	-100 ~ 500	O
031	-1 ~ 6	-0.1 ~ 0.6	-100 ~ 600	O
014	-1 ~ 9	-0.1 ~ 0.9	-100 ~ 900	O
032	-1 ~ 10	-0.1 ~ 1	-100 ~ 1,000	O
033	-1 ~ 15	-0.1 ~ 1.5	-100 ~ 1.5 MPa	O
034	-1 ~ 20	-0.1 ~2	-100 ~ 2 MPa	O
035	-1 ~ 25	-0.1 ~ 2.5	-100 ~ 2.5 MPa	O

O : Available X : Not available

Memo